

wall mount racks



NPR series

★ ★ ★

Wall mounted 9.5"/10.5" cabinet
Half rack size - 420mm depth



EPR series

★ ★ ★

Economical 19" wall rack
450 mm depth



WPR4 series

★ ★ ★ ★

19" wall mount rack
Removable back-450mm depth



WPR6 series

★ ★ ★ ★

19" wall mount rack
Removable back-450mm depth



HPR series

★ ★ ★ ★ ★

Double section 19" wall
mount rack-550mm depth

Usable depth	360 mm	370 mm	410 mm	560 mm	510 mm (adjustable)
Outer depth	420 mm	450 mm	450 mm	600 mm	550 mm
Outer width	325 mm (Half 19")	540 mm	600 mm	600 mm	600 mm
Unit heights	4,6 U	6, 9, 12 U	6, 9, 12 U	6, 9, 12 U	6, 9, 12 U
Usage	Wall mounted, shelf standing	Wall mounted, shelf standing	Wall mounted, shelf standing	Wall mounted, shelf standing	Wall mounted
Frame thickness	1.5 mm	1.5 mm	1.5 mm	1.5 mm	1.5 mm
Shelf thickness	1.2 mm	1.0 mm	1.2 mm	1.2 mm	1.2 mm
Front door	Full tempered glass	Full tempered glass	Tempered glass with steel frame	Tempered glass with steel frame	Tempered glass with steel frame
Reversible door position	✓	-	-	-	✓
Rear door	-	-	Removable rear panel	Removable rear panel	Fully hinged back
Lockable front door	✓	✓	✓	✓	✓
Lockable side panels	✓	-	✓	✓	✓
Removable sides	✓	✓	✓	✓	✓
Wheels	-	-	-	-	-
Max. load	25 kg	50 kg	60 kg	60 kg	30 kg
Assembly time	Pre-assembled	Pre-assembled	Pre-assembled	Pre-assembled	Pre-assembled

floor racks



PR series



19" rack cabinet
500mm depth



SPR6 series



19" rack cabinet
600mm width x 600mm depth



SPR8 series



19" rack cabinet
600mm width x 800mm depth



SPR10 series



19" rack cabinet
600mm width x 1000mm depth

Usable depth	475 mm	540 mm	740 mm	940 mm
Outer depth	500 mm	600 mm	800 mm	1000 mm
Outer width	540 mm	600 mm	600 mm	600 mm
Unit heights	6, 9, 12, 18 U	18, 27, 32, 42 U	18, 32, 42 U	42 U
Usage	Floor standing	Floor standing	Floor standing	Floor standing
Frame thickness	1.5 mm	2 mm	2 mm	2 mm
Shelf thickness	-	1.2 mm	1.2 mm	1.2 mm
Front door	Open front	Tempered glass with steel frame		Tempered glass with steel frame
Reversible door position	-	✓	✓	✓
Rear door	Removable rear panel	Hinged door	Hinged door	Hinged door
Lockable front door	-	✓	✓	✓
Lockable side panels	-	✓	✓	✓
Removable sides	✓	✓	✓	✓
Wheels	Optional (PR210WS)	Included	Included	Included
Max. load	200 kg	800 kg	800 kg	800 kg
Assembly time	+/- 10 min	Pre-assembled	Pre-assembled	Pre-assembled

open frame racks



TPR3xxA series



Desktop open frame rack
Adjustable angle 0°-15°



OPR3xxA series



19" in depth adjustable
open frame rack
300 ~ 450mm depth



OPR5xxA series



19" in depth adjustable
open frame rack
500 ~ 700mm depth



DPR series



4-post 19" open-frame rack
550~1015 mm depth



GPR series



19" slide-out rack
420mm depth

Usable depth	-	from 300 to 450 mm	from 500 to 700 mm	from 550 to 1015 mm	420 mm
Outer depth	300 mm	from 300 to 450 mm	from 500 to 700 mm	from 560 to 1020 mm	580 mm
Outer width	510 mm	520 mm	520 mm	514,5 mm	503 mm
Unit heights	6, 9 U	3, 6, 9, 12, 18 U	6, 9, 12 U	32, 42 U	12, 18, 24 U
Usage	Desktop standing (0° - 15° adjustable angle)	Floor standing, Wall or ceiling mounted In-furniture integration	Floor standing, Wall or ceiling mounted, In-furniture integration	Floor standing	In-furniture integration with slide-out construction
Frame thickness	2 mm	2 mm	2 mm	2 mm	3 mm
Rear door	-	-	-	-	Easy rear access
Slide out	-	-	-	-	✓
In-depth adjustment	-	-	-	✓	-
Max. load	30 kg (standing)	100 kg (standing)	100 kg (standing)	450 kg	60 kg
Assembly time	+/- 10 min	+/- 10 min	+/- 10 min	+/- 15 min	+/- 15 min